

### DESCRIPTION

**Elevation® T-Guard Tape** – Designed to provide superior protection for T-Bars during painting, spraying, and other finishing processes. It features a UV-stabilized adhesive that prevents melting to surfaces and allows for easy removal after application. T-Guard Tape is 4.5" wide to complete cover most T-Bars. It maintains the original finish and prevents contamination and discoloration throughout the project. It's manufactured with a special adhesive which is easy to apply, adheres well, and is easy to remove without residue.

### KEY BENEFITS

- **UV Stabilized:** Prevents adhesive from melting to surfaces ensuring performance up to 60 days direct exposure, even in hot, sunny environments.
- **Special Adhesive:** Ensures enough tack and sticking power during application while remaining easy to remove with no residual adhesive.
- **4.5" Wide:** Provides complete coverage of most T-Bar, reducing the need for overlapping or additional taping.
- **Durable and Flexible:** Offers excellent performance in demanding environments, to protect surfaces from alkaline runoff, paint, dirt, and more.

### APPLICATIONS

- Protects T-Bar facing during construction preserving the original surface.
- Prevents contamination from alkaline runoff, dirt, paint, etc.
- Ensures efficient and clean removal.



### TECHNICAL SPECIFICATIONS

PROPERTY	VALUE
Width	4.5 inches
Length	600 feet per roll
Adhesive	UV-stabilized, pressure-sensitive adhesive
Material	Polyethylene film
Adhesion to Steel	15 oz/inch
Tensile Strength	20 lbs/inch
Elongation	150%
Temperature Resistance	-20°F to 200°F (-29°C to 93°C)
UV Resistance	Excellent
Color	White

## APPLICATION INSTRUCTIONS

### SURFACE PREPARATION

Ensure surface is clean, dry and free of dust or contamination.  
Wipe surfaces with Acetone or Alcohol to remove manufacturing oils prior to applying T-Guard Tape.

### APPLICATION

Roll the tape over the T-Bar or surface with light, even pressure across the surface.

### REMOVAL

After project is completed, gently peel back the tape.  
The special adhesive allows clean removal without transferring adhesive or damaging surfaces.

## LIMITATIONS

- Not intended for long-term outdoor use or applications where prolonged exposure to high UV radiation is expected.
- Do not apply to surfaces that are wet or contaminated, as this may affect adhesion performance.

## PERFORMANCE DATA

T-Guard Tape is designed to offer high performance for temporary surface protection. The tape's UV resistance ensures performance up to 60 days in outdoor or high-exposure environments, while its special adhesive remains easy to remove without leaving residue.

## PACKAGING

- **Roll Dimensions:** 4.5 inches x 600 feet
- **Case Quantity:** 12 rolls
- **Core Diameter:** 3 inches, standard for tape dispensers for quick application.